




			RTS 20/6	RTS 25/10	RTS 30/10	RTS 30
MOTOR	/ MOTOR	kW	11+11	15+15	18,5 + 18,5	18,5 + 18,5
ROTATING LENGTH	/ DÖNER ELEK UZUNLUĞU	m	6	10	10	12
TOTAL LENGTH	/ TOPLAM UZUNLUK	m	7,5	11,5	11,5	13,5
ROTATING DIAMETER	/ DÖNER ELEK ÇAPI	mm	Ø 2000	Ø 2500	Ø 3000	Ø 3000
HOLE DIAMETER	/ ELEK DELİK ÖLÇÜSÜ	mm	Ø 70 - Ø 350	Ø 70 - Ø 350	Ø 70 - Ø 350	Ø 70 - Ø 350
CAPACITY	/ KAPASİTE	t/h	7,0 - 15,0	15,0 - 25,0	20,0 - 40,0	30,0 - 50,0
ROTATION SPEED	/ DÖNME HIZI	dev/dk-rpm	0,0 - 14,0	0,0 - 14,0	0,0 - 14,0	0,0 - 14,0
RECOMMENDED SPEED	/ ÖNERİLEN HIZ	dev/dk-rpm	10,0 - 12,0	10,0 - 12,0	10,0 - 12,0	10,0 - 12,0

Trommel screens are the machines which separates the waste according to predetermined sizes. This process occurs with help of the drum inside of the trommel screen which has holes with certain diameter. Availability of changing sheet metals of the drum allows the machine to sort wastes in different dimensions. We manufacture trommel screen according to required capacity and demands.

Döner elekler, içerisine yerleştirilmiş belirli ebatlarda delikleri olan bir tamburun döndürülmesi ile içerisine atılan atığı çeşitli ölçülerde ayıklayan makinelerdir. Bu sayede istenilen ebatlardaki malzemeleri ayırma işlemi gerçekleştirilmektedir. Döner elekleri kapasiteye ve ihtiyaca göre çeşitli boylarda üretiyoruz.



Robust Rifay Design
Sağlam Rifay Tasarımı Yapı



High Corrosion Resistance
Aşınmaya Karşı Dayanıklı



European Standards Safety
Avrupa Standartlarında Güvenlik

Halilbeyli OSB. Mah.
BAYOSB Enerji Cad. No:7
Kemalpaşa İzmir / Turkey

Phone : +90 232 436 38 00

www.rifay.com

info@rifay.com



Turkey
Discover
the potential



RIFAY